

Client: \_\_\_\_\_ Project: \_\_\_\_\_ Type: \_\_\_\_\_ Qty: \_\_\_\_\_

Technical Specifications

**INPUT VOLTAGE**

AC 110~277V, 347V, 480V

**FREQUENCY**

50~60HZ

**COLOR TEMPERATURE**

4000K, 5000K

**COLOR RENDERING INDEX**

75

**DISTRIBUTION**

25°, 45°, 60°, 90°

**IP RATING**

IP65

**OPERATING TEMPERATURE**

-30°C~+55°C

**LIFE SPAN**

50,000hrs

**DIMMING**

0-10V

Product Showcase




Product Features

**FEATURES**

- Equivalent to 750W - 1000W HPS luminaire.
- 4 Patented technology: HDT, FIN Fastening, Zipped-fins, Seamless Fitting
- 18° increment, 11 lockable positions, overall 170 degree adjustability
- Factory pre-treated and powder-coated to meet the most rugged industry standards.
- Built-in surge protection up to 4kV.
- IP65 Rated suitable for outdoor / wet applications.
- UL / cUL Listed.



Dimensions



A	B	C	D
497±5mm (19.57"±0.2")	303mm (11.93")	374±5mm (14.72"±0.2")	448mm (17.64")

Ordering Information

**KMHP** -    - **YM BK**

Series	Wattage	CCT	Distribution	Mounting	Finish	Input Voltage & Dimming
<b>KMHP</b>	400 - 400W (40500lm)	50 - 5000K	25 - 25°	<b>YK</b> - Yoke Mount	<b>BK</b> - Black	<b>U</b> - 110-277V <b>UD</b> - 110-277V & 1-10V Dimming <b>H</b> - 347V, 480V
	500 - 500W (58000lm)	40 - 4000K	45 - 45°			
			60 - 60°			
			90 - 90°			