

Client: _____ Project: _____ Type: _____ Qty: _____

Technical Specifications

- INPUT VOLTAGE**
AC 110~277V, 347V, 480V
- FREQUENCY**
50~60HZ
- COLOR TEMPERATURE**
4000K, 5000K
- COLOR RENDERING INDEX**
75
- DISTRIBUTION**
25°, 45°, 60°, 90°
- IP RATING**
IP65
- OPERATING TEMPERATURE**
-30°C~+55°C
- LIFE SPAN**
50,000hrs
- DIMMING**
0-10V



Product Showcase


FEATURES

- Equivalent to 750W - 1000W HPS luminaire.
- 4 Patented technology: HDT, FIN Fastening, Zipped-fins, Seamless Fitting
- 18° increment, 11 lockable positions, overall 170 degree adjustability
- Factory pre-treated and powder-coated to meet the most rugged industry standards.
- Built-in surge protection up to 4kV.
- IP65 Rated suitable for outdoor / wet applications.
- UL / cUL Listed.



Product Features

Dimensions



A	B	C	D
497±5mm (19.57"±0.2")	303mm (11.93")	374±5mm (14.72"±0.2")	448mm (17.64")

Ordering Information

KMHP - - **YM BK**

Series	Wattage	CCT	Distribution	Mounting	Finish	Input Voltage & Dimming
KMHP	400 - 400W (40500lm)	50 - 5000K	25 - 25°	YK - Yoke Mount	BK - Black	U - 110-277V UD - 110-277V & 1-10V Dimming H - 347V, 480V
	500 - 500W (58000lm)	40 - 4000K	45 - 45°			
			60 - 60°			
			90 - 90°			